## SERIES #13

This series is designed for use in indicating height of water in tanks, stand pipes, reservoirs, or hot water heating systems.

## **STANDARD FEATURES:**

**MOVEMENT\*:** Sturdy corrosive resistant bronze bushed rotary type movement with bronze links and stainless steel link screws.

**POINTER\*:** Lightweight balanced construction with adjustment feature and adjustable red set hand.

**DIAL:** Heavy gauge aluminum. 4½", 6" and 8½"

WINDOW\*: Glass.

**CONNECTION:** Brass machined connection with wrench flats, 1/4" NPT male connection at bottom or back of case.

ACCURACY: ASME/ANSI B40.1 Grade 1A (1%)

## **STANDARD RANGES:**

RANGE (Feet of water)	ORDER CODE									
0-34 ft0-15 psi	51									
0-70 ft0-30 psi	52									
0-140 ft0-60 psi	53									
0-230 ft0-100 psi	54									
0-370 ft0-160 psi	55									
0-460 ft0-200 psi	56									
0-690 ft0-300 psi	57									



	Ordering Number - Construct by selecting one item from each of the columns below:										
1	Dial Size:	2	Series Number:	3	Case Style:	4	Range Code:	5	Connection Size and Style:	6	Bourdon Tube and Socket Code:
	4½" = 4		= 13		= 1				1 = 1/4 NPT Bottom		1 = Bronze
	6" = 6				= 2				2 = 1/4 NPT Back		
	8½" = 8				= 5		See standard				
					= 6		range chart				
	Example:				= 7		for code.				
	41315511				= 7BF						
	4		13		1		55		1		1